


带轮毂型

产品特点：与标准型相比，为带轮毂结构。



DSSHA
DSSHC
带轮毂型



▲ 轴承精度 JIS B1514 0级
▲ 轴承采用压入方式

代号	材质	热处理	表面处理
DSSHA	45#	齿部高频淬火	四氧化三铁保护膜
DSSHC	304	无	无

订购编号示例 1 代号 2 尺寸系列 - 3 齿数
DSSHA06C - 16

1 代号	2 尺寸系列	3 齿数	孔径 dr	主要尺寸					轴承								
				径节 D	外径 D1	凸台直径 D2	D3	T	L	零件号	Cr(动额定负载) (kN)		D4	b			
											钢	不锈钢					
DSSHA DSSHC	06C	▲10	10	30.82	34	24.5	13	4.3	20	6700ZZ	0.85	0.68	15	4			
		▲12	12	36.8	41	30.5	18			6801ZZ	1.92	1.63	21	5			
		▲13	12	39.8	44	32	18			6801ZZ	1.92	1.63	21	5			
		14	12	42.81	47	32	21			6901ZZ	2.89	2.45	24	6			
		15	12	45.81	51	35	24			6001ZZ	5.1	4.35	28	8			
		16	12	48.82	54	37	24			6001ZZ	5.1	4.35	28	8			
		18	15	54.85	60	44	28			6002ZZ	5.6	4.76	32	9			
		20	15	60.89	66	50	28			6002ZZ	5.6	4.76	32	9			
		21	15	63.91	69	53	28			6002ZZ	5.6	4.76	32	9			
		25	20	76	81	53	34			6904ZZ	6.4	5.42	37	9			
		32	20	97.18	102	53	34			6904ZZ	6.4	5.42	37	9			
		08A	▲10	12	41.1	46	32			18	7.2	22	6801ZZ	1.92	1.63	21	5
	▲11		12	45.08	51	36	21	6901ZZ	2.89	2.45			24	6			
	▲12		12	49.07	55	40	24	6001ZZ	5.1	4.35			28	8			
	13		12	53.07	59	37	24	6001ZZ	5.1	4.35			28	8			
	14		12	57.07	63	42	24	6001ZZ	5.1	4.35			28	8			
	15		15	61.08	67	46	28	6002ZZ	5.6	4.76			32	9			
	16		15	65.1	71	50	28	6002ZZ	5.6	4.76			32	9			
	17		20	69.12	76	54	34	6904ZZ	6.4	5.42			37	9			
	18		20	73.14	80	57	34	6904ZZ	6.4	5.42			37	9			
	19		20	77.16	84	62	34	6904ZZ	6.4	5.42			37	9			
	20		25	81.18	88	67	36	6905ZZ	7.05	5.6			42	9			
	24		25	97.3	104	63	36	6905ZZ	7.05	5.6			42	9			
	25	25	101.33	108	63	36	6905ZZ	7.05	5.6	42	9						
	26	25	105.36	112	63	36	6905ZZ	7.05	5.6	42	9						
	10A	▲12	15	61.34	69	50	29	8.7	25	6202ZZ	7.75	6.5	35	11			
		14	15	71.34	79	52	29			6202ZZ	7.75	6.5	35	11			
		15	20	76.35	84	57	34			6904ZZ	6.4	5.42	37	9			
		17	20	86.39	94	67	34			6904ZZ	6.4	5.42	37	9			
		18	25	91.42	100	72	41			6005ZZ	10.1	8.59	47	12			
		20	25	101.48	110	73	41			6005ZZ	10.1	8.59	47	12			
		24	30	121.62	130	73	48			6006ZZ	13.2	11.2	55	13			
		28	35	141.79	150	73	49			6907ZZ	9.55	9.27	55	10			
		12A	12	15	73.6	83	51			29	11.7	32	6202ZZ	7.75	-	35	11
			14	20	85.61	95	62			40			6204ZZ	12.8	-	47	14
			15	20	91.62	101	68			40			6204ZZ	12.8	-	47	14
17			25	103.67	113	73	45			6205ZZ			14	-	52	15	
19	30		115.74	126	83	55	6206ZZ	19.5	-	62			16				
20	30		121.78	132	83	55	6206ZZ	19.5	-	62			16				
22	30		133.86	144	83	55	6206ZZ	19.5	-	62			16				
25	35		151.99	162	83	60	6207ZZ	25.7	-	72			17				
30	35		182.25	193	83	60	6207ZZ	25.7	-	72			17				

▲带有▲的产品在轮毂外径上带有槽口