


精巧型

产品特点: 与 ED 标准型相比, 结构紧凑, 但相同内径的情况下外径较小, 额定负荷较小, 适合安装空间紧凑的情况。



EDC
精巧型

| 主体材质 | 表面处理 |
|------|------|
| 45# | 光饰 |

⚠ 若有特殊需求, 可提供 45# 无电解镀锌、SUS304 材质的同规格产品, 具体请与销售人员联系。

订购编号示例

1 代号 - 2 内径 dr × 3 外径 D
EDC - 19 × 41

| 1 代号 | 主要尺寸 | | | | 额定负荷 | | 接触面压强 | | 内六角螺钉 | | 螺钉锁紧扭矩 (N·m) | |
|------|------|-----|------|----------------|----------|----------|---------|---------|-------|-----|--------------|----|
| | 内径 | 外径 | L | L ₁ | 轴向力 (KN) | 扭矩 (N·m) | 轴 (Mpa) | 毂 (Mpa) | 数量 | 规格 | Ts | |
| | 2 dr | 3 D | | | Ft | Mt | Ps | Ph | | | | |
| EDC | 16 | 32 | 22 | 18 | 8 | 66 | 93 | 47 | 4 | M4 | 5.1 | |
| | 18 | 40 | | | | 165 | 185 | 83 | | | | |
| | 19 | 41 | | | | 174 | 176 | 81 | | | | |
| | 20 | 42 | | | | 183 | 167 | 79 | | | | |
| | 22 | 44 | 201 | | 152 | 76 | | | | | | |
| | 24 | 46 | 329 | | 209 | 109 | | | | | | |
| | 25 | 47 | 343 | | 200 | 106 | | | | | | |
| | 28 | 50 | 384 | | 179 | 100 | | | | | | |
| | 30 | 52 | 412 | 167 | 96 | | | | | | | |
| | 32 | 54 | 439 | 156 | 93 | | | | | | | |
| | 35 | 57 | 480 | 117 | 72 | | | | | | | |
| | 36 | 58 | 28 | 21.5 | 36.5 | 659 | 151 | 94 | 6 | M6 | 17 | |
| | 38 | 60 | | | | 695 | 143 | 91 | | | | |
| | 40 | 62 | | | | 732 | 136 | 88 | | | | |
| | 42 | 70 | | | | 1427 | 185 | 111 | | | | |
| | 45 | 73 | 1529 | | 172 | 106 | | | | | | |
| | 48 | 76 | 1631 | | 161 | 102 | | | | | | |
| | 50 | 78 | 1699 | | 155 | 99 | | | | | | |
| | 55 | 83 | 1869 | | 141 | 93 | | | | | | |
| | 60 | 88 | 2039 | 129 | 88 | | | | | | | |
| | 65 | 93 | 36 | 28 | 68 | 2208 | 93 | 65 | 8 | M8 | 42 | |
| | 70 | 105 | | | | 3759 | 137 | 91 | | | | |
| | 75 | 110 | | | | 4027 | 128 | 87 | | | | |
| | 80 | 115 | | | | 4296 | 120 | 83 | | | | |
| 85 | 120 | 45 | 35 | | 107 | 5705 | 141 | 100 | 10 | M10 | | 83 |
| 90 | 125 | | | | | 6041 | 133 | 96 | | | | |
| 95 | 130 | | | | | 6372 | 120 | 87 | | | | |
| 100 | 138 | | | | | | | | | | | |

⚠ 与胀紧套连接的轴和孔精度要求分别为 h8 和 H8