


标准型

■ 产品特点: 拧紧圆螺母就可完成安装, 适用于中小直径的轴与轮毂联接, 将配套的垫圈锁紧圆螺母后可防止胀紧套轴向移动, 保持扭矩传递的可靠性, 即使轮毂内孔轴向长度略小于尺寸 h 也可安装使用。



ESM
标准型

主体材质	表面处理
45#	光饰

⚠ 若有特殊需求, 可提供 45# 无电解镀锌、SUS304 材质的同规格产品, 具体请与销售人员联系。

⚠ 符合国标 JB/T 7934-1999 Z19A 胀紧套标准

订购编号示例 1 代号 - 2 内径 dr × 3 外径 D
ESM - 15 × 25

1 代号	主要尺寸					额定负荷		接触面压强		开槽螺母		螺钉锁紧扭矩	
	内径 2 dr	外径 3 D	D1	H	h1	轴向力	扭矩	轴	毂	螺距	规格	Ts	
						Ft	Mt	Ps	Ph				
ESM	14	25	32	16.5	6.5	5.1	38	200	110	1	M20	95	
	15	25				5.5	41	185	110			95	
	16	25				5.45	43	174	110			95	
	17	26				5.5	47	164	107			95	
	18	26				5.4	49	155	107			95	
	18	30				6.6	58	185	112			160	
	19	30	6.6	62		176	112	160					
	20	30	6.6	66		167	111	160					
	22	32	6.6	73		152	105	160					
	24	35	45	18		18	8.75	105	185	127	1.5	M30	220
	25	35					8.8	110	178	127			220
	28	36					8.55	120	159	124			220
	28	40			10.6		149	188	141	340			
	30	40			10.6		160	164	123	340			
	32	42			10.6		170	154	117	340			
	35	45	52	19.5	7		13.1	230	153	120	1.5	M36	480
	36	45					13.3	240	149	120			480
	38	48					13.1	250	141	112			480
	38	50					13.1	250	141	112			480
	40	50					15.5	310	124	93			680
	42	55					15.2	320	114	87			680
	45	55	70	25.5		10	17.7	400	122	96	1.5	M50	870
	45	57					17.7	400	122	96			870
	48	60					20.8	500	135	105			970
	50	60					20.8	520	130	105			970
	50	62					20.8	520	130	105			970
	55	65					22	610	103	84			1100
	55	68	80	27.5	12		22	610	103	84	2	M60	1100
	56	68					22	620	101	82			1100
	60	70					26.6	800	113	93			1300
	60	73					26.6	800	113	93			1300
	63	79					31.1	980	107	86			1600
65	79	31					1010	104	86	1600			
70	84	92	30.5	14		31	1010	104	86	2	M70	1600	
70	84					35.4	1240	110	92			2000	

⚠ 与胀紧套连接的轴和孔精度要求分别为 h8 和 H8