


中重载型



SCEMHP
平行向

订购编号示例

1 代号 - **2** D - **3** L
SCEMHP - 5 - 20

1 代号	2 D	3 L	d	动态负载时		初拉力 (N)	刚度系数 (N/mm)
				工作行程 S (mm)	工作极限载荷 (N)		
SCEMHP	3	10	0.45	2.2	6.47	1.57	2.26
		15		4.5			1.08
		20		6.7			0.74
		25		9.1			0.54
		30		11.4			0.43
	4	15	0.55	4.5	8.43	1.86	1.47
		20		7.1			0.93
		25		10			0.66
		30		12.6			0.52
		35		15.2			0.43
	5	15	0.7	3.9	14.71	2.45	3.14
		20		6.9			1.77
		25		9.6			1.28
		30		12.5			0.98
		35		15.6			0.78
		40		19.2			0.64
		45		21.9			0.56
	6	20	0.9	3.9	23.54	5.88	4.51
		25		6			2.94
		30		7.8			2.26
		35		10			1.77
		40		12			1.47
		45		13.8			1.28
		50		16.4			1.08
		55		18			0.98
	8	25	1.1	5.8	31.38	6.86	4.23
		30		8.3			2.94
		35		10.9			2.26
40		13.2		1.86			
45		15.6		1.57			
50		18.5		1.32			
55		21.7		1.13			
60		23.8		1.03			
65		26.3		0.93			
70		27.8		0.88			

1 代号	2 D	3 L	d	动态负载时		初拉力 (N)	刚度系数 (N/mm)
				工作行程 S (mm)	工作极限载荷 (N)		
SCEMHP	10	30	1.4	6.5	49.03	12.75	5.58
		35		8.7			4.17
		40		10.7			3.39
		45		12.9			2.81
		50		15.2			2.39
		60		17.2			2.11
		70		19.5			1.86
		80		23.1			1.57
		90		27.4			1.32
		100		32.1			1.13
	12	35	1.8	5	83.36	23.54	12.00
		40		7			8.55
		45		9			6.65
		50		11			5.44
		55		13			4.60
		60		14.5			4.13
		70		17.8			3.36
		80		21.3			2.81
		90		24.5			2.44
		100		27.5			2.18

△初拉力、刚度系数为参考值。载荷 (kgf) = 载荷 N × 0.101972

代号	类型	材质
SCEMHP	中重载型	SWP-A/B